

accepting television (TV) broadcast signals, wherein said TV signals are based on a multitude of standards, including, but not limited to, National Television Standards Committee (NTSC) broadcast, PAL broadcast, satellite transmission, DSS, DBS, or ATSC;

tuning said TV signals to a specific program;

providing at least one Input Section, wherein said [input section] Input Section converts said specific program to an Moving Pictures Experts Group (MPEG) formatted stream for internal transfer and manipulation;

*A1  
concl.* providing a Media Switch, wherein said Media Switch parses said MPEG stream, said MPEG stream is separated into its video and audio components;

storing said video and audio components on a storage device;

providing at least one Output Section, wherein said Output Section extracts said video and audio components from [a] said storage device;

wherein said Output Section assembles said video and audio components into an MPEG stream;

wherein said Output Section sends said MPEG stream to a decoder;

wherein said decoder converts said MPEG stream into TV output signals;

wherein said decoder delivers said TV output signals to a TV receiver; and

accepting control commands from a user, wherein said control commands are sent through the system and affect the flow of said MPEG stream.

*A2* 21. (first amended) The process of claim 1, wherein [a] said storage device is connected to said Media Switch.

*A3* 25. (first amended) The process of claim 24, wherein said user queues up programs from said [disk] storage device to be stored on said recording device.

*A4* 30. (first amended) The process of claim 24, wherein the output of said recording device is routed to said [input section] Input Section, allowing said recording device to act as a storage back up system, said recording device accepts overflow storage, TV programs, software updates, or other data that are later retrieved and sent to said [input section] Input Section.

32. (first amended) An apparatus for the simultaneous storage and play back of multimedia data, comprising:

a module for accepting television (TV) broadcast signals, wherein said TV signals are based on a multitude of standards, including, but not limited to, National Television Standards Committee (NTSC) broadcast, PAL broadcast, satellite transmission, DSS, DBS, or ATSC;

A5 a module for tuning said TV signals to a specific program;

at least one Input Section, wherein said [input section] Input Section converts said specific program to an Moving Pictures Experts Group (MPEG) formatted stream for internal transfer and manipulation;

a Media Switch, wherein said Media Switch parses said MPEG stream, said MPEG stream is separated into its video and audio components;

a module for storing said video and audio components on a storage device;

at least one Output Section, wherein said Output Section extracts said video and audio components from [a] said storage device;

wherein said Output Section assembles said video and audio components into an MPEG stream;

wherein said Output Section sends said MPEG stream to a decoder;

wherein said decoder converts said MPEG stream into TV output signals;

wherein said decoder delivers said TV output signals to a TV receiver; and

accepting control commands from a user, wherein said control commands are sent through the system and affect the flow of said MPEG stream.

A6 52. (first amended) The apparatus of claim 32, wherein [a] said storage device is connected to said Media Switch.

A7 55. (first amended) The apparatus of claim 54, wherein said user queues up programs from said [disk] storage device to be stored on said recording device.

A8 60. (first amended) The apparatus of claim 54, wherein the output of said recording device is routed to said [input section] Input Section, allowing said recording